LCPC150-12 Valve Regulated Sealed Gel Battery



Specifications

Battery Model	LCPC150-12 12V150Ah			
Design Life (years, 25℃)	10			
Capacity (Ah, 25℃)	10HR (15A, 1.80V)	5HR (24.9A, 1.80V)	3HR (36.75A, 1.80V)	1HR (81.3A, 1.75V)
	150	124.5	110.25	81.3
Dimensions (mm)	Length	Width	Height	Total Height
	483	171	240	240
Approx. Weight (kg)	42.5			
Reference Internal Resistance (mΩ)	3.6 (fully charged @ 25℃)			
Maximum Discharge Current (A)	450			
Self-Discharge (25℃)	⩽1.5% per months			
Charge Voltage (V/cell, 25℃)	Cycle use		Float use	
	2.40(-3.5mV/℃/cell), max charge current: 30A		2.27(-3.5mV/℃/cell)	
Short Circuit Current (A)	3300			

Discharge Data

Constant Current Discharge Data (25℃, A)

End VoltAge (V/cell)	h								
	1	3	5	10	20	50	100	120	240
1.70	83.55	38.70	26.18	15.35	7.850	3.330	1.740	1.470	0.780
1.75	81.30	37.95	25.65	15.20	7.725	3.270	1.710	1.449	0.765
1.80	78.75	36.75	24.90	15.00	7.600	3.195	1.680	1.425	0.750
1.85	75.75	35.40	24.00	14.70	7.450	3.105	1.635	1.389	0.735
1.90	72.00	33.75	22.95	14.30	7.250	3.000	1.590	1.350	0.720

Constant Power Discharge Data (25℃, W)

End VoltAge (V/cell)	h								
	1	3	5	10	20	50	100	120	240
1.70	150.50	63.20	45.50	28.30	14.700	7.130	3.850	3.270	1.650
1.75	145.50	62.10	44.40	28.00	14.450	7.050	3.670	3.210	1.620
1.80	141.50	61.10	43.20	27.70	14.200	6.750	3.420	3.090	1.590
1.85	137.00	60.30	42.20	27.10	13.900	6.390	3.250	2.890	1.530
1.90	133.20	59.40	41.00	26.70	13.700	6.150	3.110	2.790	1.500

LCPC150-12 Valve Regulated Sealed Gel Battery

Performance Curve

Trickle(or Float) Service Life



Charge Characteristic



Cycle Service Life



Discharge Characteristic



FEATURES

- Low self-discharge and long shelf life
- Non-Spillable construction
- Safety valve installation for explosion proof
- Exceptional deep discharge recovery performance
- 99.7% pure lead calcium grids and A recognized Component of U.L

APPLICATION

- Photovoltaic system
- Telecommunications
- Emergency Power System
- Power plant and power transformer system
- Control Equipment

- IEC 60896-21/22
- DIN 40742
- YD/T 1360-2005

ISO 9001